



The LiMAR® LQK is a connection which can be assembled and disassembled safely, in a rapid motion without the use of pipe wrenches.

The LQK male is first aligned & inserted into the LQK female. The connection is then rotated 90 degrees to allow the spring loaded locking plate to drop into a slotted profile at the top of the male connection end. This prevents the connection from rotating in either direction

For disassembly, a pin punch is inserted through the locking plate via an access hole in the female connection. Levering the pin punch raises the locking plate from the slot to allow the connection to rotate 90 degrees. Once the profile is aligned both LQK connections can be safely separated.



## **TOOL APPLICATIONS:**

• Used as a safe, fast and efficient method of connecting toolstring components together without the use of pipe wrenches

## **DESIGN FEATURES & BENEFITS:**

• Available in all nominal toolstring sizes including 1-1/4"

• 100% compatible with other manufacturers' Quick Lock Connections

• Laser cut, sour service locking plates for enhanced performance

## LIMAR LQK vs SUCKER ROD:

• **SAFE** Reduced risk of injury during use

Reduced exposure to potential injury Zero risk of injury from pipe wrench use


• **RELIABLE** Will not 'back-off' down hole

Minimal working parts

Stronger

• COST EFFECTIVE Longer working life

Dramatic time saving in operation Ease of redress with no complex parts



## TECHNICAL DATA

Assembly Part No.	LQK Nominal OD	Actual OD	Fish Neck	Male Connection Code	Female Connection Code
1008-XXXM-XXXF-RX	1-1/4"	1.250"	1.187"	146M	146F
1008-XXXM-XXXF-RX	1-1/2"	1.500"	1.375"	047M	047F
1008-XXXM-XXXF-RX	1-1/2"	1.750"	1.375"	047M	047F
1008-XXXM-XXXF-RX	1-7/8"	1.875"	1.750"	048M	048F
1008-XXXM-XXXF-RX	1-7/8"	2.125"	1.750"	048M	048F
1008-XXXM-XXXF-RX	2-1/2"	2.500"	2.312"	049M	049F

XXX - Denotes connection type

For additional sizes or further information please contact sales@limaroiltools.com