



## MULTI ROLLER WHEEL SUB

The **LiMAR**<sup>®</sup> Multi Roller Wheel Sub can be positioned at various points along the length of a toolstring to effectively lift the string from off of the tubing wall and onto the roller wheels.

The LiMAR<sup>®</sup> design is short and compact with six roller wheels per assembly - each offset at 60 degrees to each other.


The roller wheels rotate freely on hardened axles to reduce friction which is commonly known as 'drag'. Particularly in highly deviated wells, drag occurs between the full contact area of the toolstring and the tubing wall.

**TOOL APPLICATIONS:**

- For use in high angle, deviated wells
- Ideal for tool centralisation within larger ID tubing

**DESIGN FEATURES & BENEFITS:**

- Short, compact design
- Available in a range of sizes to suit all completion designs
- Hardened axles and wheels with replaceable bushings
- Connection options to suit customer requirements
- Selected components QPQ treated
- Hexagonal flats for safe make-up & break-out



**TECHNICAL DATA**

Assembly Part No.	Nominal OD	Effective Roller OD	Fish Neck	Connection
1144-1250-XXXX-XXX-RX	1.250"	Optional	1.187"	Optional
1144-1500-XXXX-XXX-RX	1.500"	Optional	1.375"	Optional
1144-1875-XXXX-XXX-RX	1.875"	Optional	1.875"	Optional
1144-2500-XXXX-XXX-RX	2.500"	Optional	2.313"	Optional

XXXX - Denotes effective roller OD  
 XXX- Last 3 digits of part number denotes connection type  
 For additional sizes or further information please contact [sales@limaroiltools.com](mailto:sales@limaroiltools.com)