



LEAD IMPRESSION BLOCK

The LiMAR® Lead Impression Block (LIB) is designed to provide a simple but effective means of taking an imprint of a downhole device or obstruction. By a single, downward jar against the obstruction, the soft lead face is imprinted after impact.

After removing the Lead Impression Block at surface the indentation can be interpreted to provide an indication as to the cause and type of obstruction within the well.

The interpreted results allow for subsequent fishing operations to be performed to enable fish recovery.



TOOL APPLICATIONS:

• To provide a simple means of taking an imprint of a downhole device or obstruction

DESIGN FEATURES & BENEFITS:

- Available in a range of sizes to suit all Completion designs
- Double face designs available for flow control device diagnostics
- Connection options to suit customer requirements
- Selected components QPQ treated
- Hexagonal flats for safe make-up & break-out



TECHNICAL DATA

Assembly Part No.	Nominal Tubing Size	To Suit Sizes Up To	Fish Neck	Connection
1036-XXXX-XXX-RX	2-3/8"	2.000"	Optional	Optional
1036-XXXX-XXX-RX	2-7/8"	2.500"	Optional	Optional
1036-XXXX-XXX-RX	3-1/2"	3.000"	Optional	Optional
1036-XXXX-XXX-RX	4-1/2"	4.000"	Optional	Optional
1036-XXXX-XXX-RX	5-1/2"	5.000"	Optional	Optional
1036-XXXX-XXX-RX	7" to 10-3/4"	8.470"	Optional	Optional

XXXX - Denotes OD

XXX - Last 3 digits of part number denotes connection type

For additional sizes or further information please contact sales@limaroiltools.com